

# Medical Pharmaceutical Refrigerator

# MPR 110V



## TECHNICAL CHARACTERISTICS:

- **Structure** : upright type, underbench fitting, realized in sheet steel epoxy coated white colour outside and stainless steel 18/10 AISI 304 inside. All the internal corners are rounded to make easy any cleaning operations and the internal bottom is tray type to contain spills
- **Insulation** : high density (40 Kg/m<sup>3</sup>) foamed-in-place polyurethane, with a thickness of 40 mm. CFC-free
- **Feet** : Nr 4, adjustable in height for levelling
- **Glass door** : Nr. 1, hinged, made a perimetrical aluminium frame and three layers of tempered insulating glass, with vacuum among the glass layers in order to increase the insulating rate. The door is provided with a removable magnetic rubber gasket in order to grant a perfect hermetic closing. The handle is realized in aluminium and it is fixed in the top part of the door. The door is also fitted with a spring loaded automatic closing device for openings inferior then 90° and special door switch that stops the internal ventilation at the door opening (to limit the air cold loss)
- **Internal equipment** : Nr 1, storage open wire shelf realized sheet steel with a strong plastic coating (rust-proof material) . The shelf is mounted on special anti-tilt stainless steel slides that allows the shelf extraction and it can be easily removed and adjusted in

height without the use of any tool. The special internal racking-system allows a great flexibility of the internal fitting with the possibility of interchange and combine both shelves and drawers (drawers optionally available)

- Shelf dimensions (W x D cm) : 46 x 47
- Shelf loading capability (Kg) : 30 (with uniformly stored material)
- **Control panel** : located in the bottom part of the structure, it is compounded by the main switch and digital electronic thermostat with incorporated alarm
  - Main switch : appliance's ON/OFF switch, adjustable in 2 positions, it became illuminated when on the position ON
  - Digital electronic thermostat with incorporated alarm : microprocessor operating, with 4 switches, allowing the control of all the refrigerator functions (maintaining of the setted temperature, defrostings, compressor and fans functioning). The internal temperature is displayed with a LED display, with red colour, bright indication and an accuracy of 0,1°C. Into its functions, the thermostat includes even an alarm, both acoustic (with a buzzer) and visual (with indication LED dots) for temperature deviations, both over or below than the programmed one, with limits that remains adjustable according to the user needs. The acoustic alarm can be even muted through a special switch
- **Cooling unit** : bottom mounted, with the condensing unit compounded by Nr 1 hermetic compressors and Nr 1 finned condenser, air cooled through a fan. Also, in the rear side of the storage chamber, is mounted the finned evaporator with copper pipes protected from a pierced stainless steel cover that incorporate the fan. All the mounted components are industrial grade to grant the maximum reliability
- **Refrigerant** : R134a CFC-free
- **Refrigeration** : forced-air, through a fan, granting the maximum temperature uniformity and stability inside of the cabinet
- **Defrosting** : completely automatic, thermostat controlled. The condensate water is automatically channelled into an heated tray, located in the motor compartment, for the automatic evaporation of the condensate water
- **Temperature range** : infinitely adjustable between +2°C / +15°C
- **Voltage (V/ph/Hz)** : 220-230/1/50
- **Plug** : Schuko type
- **Breakers** : Nr 2 glass cartridge fuses with a rating of 10A, at protection of the appliance
- **Noise level (dB(A))** : ≤ 48
- **Gross capacity (litres)** : 115
- **Net capacity (litres)** : 110
- **Dimensions (W x D x H cm)** : 62 x 66 x 83
- **Net weight (Kg)** : 60
- **Packed dimensions (W x D x H cm)** : 70 x 75 x 105 (0,55 m<sup>3</sup>)
- **Gross weight (Kg)** : 70

# Medical Pharmaceutical Refrigerator

# MPR 110V

## ACCESSORIES AVAILABLE:

- Extra wire shelf
- Front top for drawer
- Temperature chart recorder
- Cable port with cover
- Stainless steel drawers
- Kit of rollers
- Electronic temperature printer
- Different voltage
- Plastic partition for drawer
- Safety door lock with key
- Internal electrical socket
- Wooden crate packing



\* The declared performances are referred at +35°C ambient temperature, relative humidity of 70% and without any internal thermal mass (empty cabinet).

\* Should it be necessary or useful without undermining any model essential features, technical and stylistic characteristics are subject to be changed without manufacturer's previous notice.