

# Laboratory combined Refrigerator/Freezer

# LCRF 1365



## TECHNICAL CHARACTERISTICS:

- **Structure** : upright type, realized in stainless steel 18/10 AISI 304 both in- and outside. The storage compartment is divided vertically into 2 storage compartments fully insulated and completely independent between them, in the right door, the refrigerator compartment, while at the left door, the freezer. All the internal corners are rounded to make easy any cleaning operations and the internal bottom is tray type to contain spills
- **Insulation** : high density (40 Kg/m<sup>3</sup>) foamed-in-place polyurethane, with a thickness of 60 mm. CFC-free
- **Feet** : Nr 4 made in stainless steel 18/10 AISI 304, adjustable in height for levelling
- **Insulated door** : Nr 2, hinged, side-by-side, all made with the same material and insulation as the rest of the structure (stainless steel 18/10 AISI 304 always both in- and outside). Both the doors are provided with a removable magnetic rubber gasket in order to grant a perfect hermetic closing. The handles are flush-fitting type so they do not increase the size of the refrigerator. Both the doors are also fitted with a spring loaded automatic closing device for openings inferior 90° and with a special door switches that stops the internal ventilation at the door opening (to limit the air cold loss) and light the internal lighting at every opening
- **Internal equipment** : Nr 6, (3 for each door), storage open wire shelves realized sheet steel with a strong plastic coating (rust-proof material). The shelves are mounted on special anti-tilt stainless steel slides that allows the shelf extraction and they can be easily removed and adjusted in height without the use of any tool. The special internal racking-

system allows a great flexibility of the internal fitting with the possibility of interchange and combine both shelves and drawers (drawers optionally available)

- Shelf dimensions (W x D cm) : 53 x 65
- Shelf loading capability (Kg) : 35 (with uniformly stored material)
- **Internal lighting** : Nr 2 bulbs, one for each door, both mounted in the bottom part of the control panel, with automatic activation at every door opening through a special switch
- **Control panels** : Nr 2, one for each compartment, both located in the top part of the structure (above the doors) and both including the main switch and digital electronic thermostat with incorporated alarm
  - Main switch : appliance's ON/OFF switch, adjustable in 2 positions, it became illuminated when on the position ON
  - Digital electronic thermostat with incorporated alarm : microprocessor operating, with 4 switches, allowing the control of all the refrigerator functions (maintaining of the setted temperature, defrostings, compressor and fans functioning). The internal temperature is displayed with a LED display, with red colour, bright indication and an accuracy of 0,1°C. Into its functions, the thermostat includes even an alarm, both acoustic (with a buzzer) and visual (with indication LED dots) for temperature deviations, both over or below than the programmed one, with limits that remains adjustable according to the user needs. The acoustic alarm can be even muted through a special switch
- **Cooling unit** : Nr 2, one for each compartment, both top mounted, completely independent between them. Each condensing unit is compounded by Nr 1 hermetic compressors and Nr 1 finned condenser, air cooled through a fan. Also, in the ceiling of each storage chamber, is mounted the finned evaporator with copper pipes, that is housed into a plastic cover that incorporate the fan. All the mounted components are industrial grade to grant the maximum reliability
- **Refrigerant** : R404a CFC-free
- **Refrigeration (both compartments)** : forced-air, through a fan, granting the maximum temperature uniformity and stability inside of the cabinet
- **Defrosting (both compartments)** : completely automatic, thermostat controlled. The condensate water is automatically channelled into a tray, with manual emptying, located under the cabinet
- **Temperature range** : REFRIGERATOR COMP. : adjustable between +2°C / +12°C  
: FREEZER COMP. : adjustable between -5°C / -25°C
- **Voltage (V/ph/Hz)** : 220-230/1/50
- **Plug** : Schuko type (Nr 2, one for each compartment)
- **Breakers** : Nr 4 glass cartridge fuses with a rating of 10A and 16A, at protection of the appliance

# Laboratory combined Refrigerator/Freezer

# LCRF 1365

- **Noise level (dB(A))** : ≤ 52
- **Gross capacity (litres)** : REFRIGERATOR COMP. : 700  
: FREEZER COMP. : 700
- **Net capacity (litres)** : REFRIGERATOR COMP. : 625  
: FREEZER COMP. : 625
- **Dimensions (W x D x H cm)** : 144 x 80 x 200
- **Net weight (Kg)** : 230
- **Packed dimensions (W x D x H cm)** : 150 x 88 x 212 (2,80 m<sup>3</sup>)
- **Gross weight (Kg)** : 280

## ACCESSORIES AVAILABLE:

- |                              |                                                              |                              |
|------------------------------|--------------------------------------------------------------|------------------------------|
| – Extra wire shelf           | – Extra stainless steel wire shelf                           | – Open wire basket           |
| – Stainless steel drawers    | – Plastic partition for drawer                               | – Front top for drawer       |
| – Kit of castors             | – Tray for the automatic evaporation of the condensate water | – Safety door lock with key  |
| – Temperature chart recorder | – Electronic temperature printer                             | – Internal electrical socket |
| – Cable port with cover      | – Different voltage                                          | – Wooden crate packing       |



\* The declared performances are referred at +32°C ambient temperature, relative humidity of 70% and without any internal thermal mass (empty cabinet).

\* Should it be necessary or useful without undermining any model essential features, technical and stylistic characteristics are subject to be changed without manufacturer's previous notice.