

Portable Refrigerator-Freezer **PRF 80**



TECHNICAL CHARACTERISTICS:

- **Structure** : completely in undeformable (UVA resistant), shock-proof, plastic material grey/black colour outside and aluminium coated white colour inside. All the internal corners are rounded to make easy any cleaning operation
- **Insulation** : high density (40 Kg/m³) foamed-in-place polyurethane, with a thickness of 35 mm. CFC-free. Thanks to the high thickness value, the refrigerator maintains the internal temperature for long time (also when it is not connected to any electrical source)
- **Handles** : Nr 2, external at the 2 sides of the structure, allowing an easy handling of the portable refrigerator
- **Insulated lid** : Nr 1, hinged, made with the same material and insulation as the rest of the structure (plastic material black colour). The lid is fitted up with a perimetric gasket and with a special

locking device (granting a perfect seal). The lid can be even removed in order to make easy the loading/unloading operations

- **Internal equipment** : Nr 1 open wire basket made in sheet steel white coated, to make easy the handling of the stored material
- **Internal lighting** : Nr 1 bulb, mounted into the storage chamber, with automatic activation at every lid opening through a special switch
- **Control panel** : located in the upper part of the structure (at the side of the lid) is compounded by the following controls:
 - Main switch : with soft-touchpad button
 - Setting switches : 2 soft-touchpads (+ or -) to adjust the temperature to the desired value
 - LCD display showing the actual internal temperature of the box
 - Power warning lamp : signalling when the appliance is connected to a power source
 - Error warning lamp : signalling abnormal working situation (i.e. condenser or compressor temperature too high, vehicle battery discharged, wrong electrical connection, etc.)
- **Cooling unit** : mounted in the lower part of the box, with the condensing unit compounded by Nr 1 hermetic compressor and Nr 1 finned condenser, air cooled through a fan. Also, the internal walls of the storage chamber are the evaporator, for a direct cooling of the stored material and granting a better temperature uniformity and stability due to the fact that the cold comes from 4 sides. All the mounted components are industrial grade to grant the maximum reliability
- **Refrigerant** : R134a CFC-free
- **Defrosting** : manual
- **Refrigeration** : static with the evaporator in 4 sides of the internal chamber, granting the maximum temperature uniformity and stability inside the box
- **Temperature range** : infinitely adjustable between -18°C / +10°C
- **Voltage (V – V/ph/Hz)** : 12 and 24 – 110-230/1/50-60
- **Plug** : the portable refrigerator includes Nr 2 electrical cords, one ending with the cigar lighter connector and the other one ending with a Schuko type plug
- **AC-DC adapter** : incorporated into the structure of the box, allow its use with all the possible different voltages, simply changing the electrical cords (supplied) to one of the 2 suitable connectors fitted in the external side of the box itself
- **Breakers** : Nr 1 glass cartridge fuse with a rating of 5A, at protection of the appliance
- **Noise level (dB(A))** : ≤ 44
- **Net capacity (litres)** : 80
- **Dimensions (W x D x H cm)** : 79 x 50 x 46
- **Net weight (Kg)** : 31
- **Packed dimensions (W x D x H cm)** : 90 x 60 x 60
- **Gross weight (Kg)** : 34

Portable Refrigerator-Freezer

PRF 80

ACCESSORIES AVAILABLE:

- Wooden crate packing



* The declared performances are referred at +32°C ambient temperature, relative humidity of 70% and without any internal thermal mass (empty cabinet).

* Should it be necessary or useful without undermining any model essential features, technical and stylistic characteristics are subject to be changed without manufacturer's previous notice.

EVERmed Srl Via Aldo Moro 25, 46020 Pegognaga (MN) – ITALY Tel.: +39 0376 550828 Fax: +39 0376 550831

E-mail: evermed@evermed.it - Http: www.evermed.it