

PLASMA/BLAST FREEZER

- ☐ Chest type
- ☐ Inside temperature ranging from -10°C~-86°C and can be set freely
- ☐ controlling precision is 1°C
- ☐ Stainless steel interior. Outer panel is from painted steel.
- ☐ Rotatable assistant door handle.
- ☐ 200mm extra thick heat insulating layer, two times foaming technology.
- ☐ Danfoss compressor. Air circulation.
- ☐ Fan electromotor EBM(made in Germany)
- ☐ Digital temperature display
- ☐ Keyboard lock and password protected configuration page
- ☐ Audible and visual alarm: High or low temperature alarm, Power failure alarm, Low battery alarm, Door ajar alarm, Filter blocking alarm, system failure alarm
- ☐ With temperature printer that records 7 days data. 72h battery backup for printer and controller display.
- ☐ 4 Casters for easy handling
- ☐ Mixture gas with R134a,R404a,R23,R24,N2,R600a and more, CFC free
- ☐ Certificate: ISO9001, ISO14001,ISO13485
- ☐ Power supply: 380V /50Hz -3 phase,
- ☐ Optional: basket
- ☐ Freeze 120bags of 200ml plasma. Surrounding temperature is 25C. 120 minutes to come to -20C, 150minutes to come to -35C, 200minites to come to -60C

Model	Capacity	External size. (WxDxH) mm	Inside size (WxDxH) mm	Input power	Weight (N.t / G.t)
DW-HW258SD	258lt	890x2085x1009	470x1120x490	4500W	330/360KG



Μοναστηρίου 7, 14565 Άγιος Στέφανος