

Οριζόντιος Υπέρ-Καταψύκτης -135°C

- ☐ Inside temperature ranging from -10°C -135°C can be set freely.
- ☐ controlling precision is 1°C
- ☐ Stainless steel interior. Outer is painted steel panel
- ☐ Rotatable assistant door handle. Door with key lock.
- ☐ 155mm extra thick heat insulating layer
- ☐ Danfoss compressor. Two compressors in parallel connection, to reduce noise and improve the cooling temperature come to -105°C steady.
- ☐ 3-4 hours to reach -135°C.
- ☐ Fan electromotor EBM(made in Germany)
- ☐ Digital temperature display
- ☐ Keyboard lock and password protected configuration page
- ☐ Audible and visual alarm: High or low temperature alarm, Power failure alarm, Low battery alarm, Door ajar alarm, Filter blocking alarm, system failure alarm
- ☐ With temperature printer that records 7 days data .72 hour battery backup for printer and controller display.
- ☐ 4 casters for easy handling
- ☐ Power supply: 220V /50Hz 1 phase
- ☐ Optional: chart recorder, CO2 back up, storage racks, boxes.
- ☐ Mixture gas with R134a,R404a,r23,R24,N2,R600a and more CFC free
- ☐ Certificate:ISO9001,ISO4001,ISO13485

Model	Capacity	External size. (WxDxH) mm	Inside size (WxDxH) mm	Input power	Weight (N.t / G.t)
DW-LW138	138lt	890x1320x1009	470x570x490	1000W	215/250KG
DW-LW328	328lt	890x2005x1009	470x1200x582	1800W	330/360KG



Μοναστηρίου 7, 14565 Άγιος Στέφανος