



BASIC LABORATORY FREEZER GLASS DOOR

BLFG 640



- **Structure** : upright type, realized in sheet steel epoxy coated white colour (rust-proof material) outside and atoxic plastic material inside. All the internal corners are rounded to make easy any cleaning operations
- **Insulation** : high density (40 Kg/m³) foamed-in-place polyurethane, with a thickness of 50 mm. CFC-free
- **Feet/Rollers** : Nr 2 feet, adjustable in height for levelling, mounted in the front side and Nr 2 rollers mounted in the back side, to make easy any moving required
- **Glass door** : Nr. 1, hinged, made a perimetrical aluminium frame white colour and three layers of heated tempered insulating glass, with vacuum among the glass layers in order to increase the insulating rate and heating film for the full door height to prevent condensation and frost. The door is provided with a removable magnetic rubber gasket in order to grant a perfect hermetic closing. The handle is incorporated in the door frame and it is flush-fitting type so does not increase the size of the refrigerator. The door is also fitted with a spring loaded automatic closing device for openings inferior then 90°
- **Internal equipment** : Nr 3, storage open wire shelves realized sheet steel with a strong plastic coating (rust-proof material) . The shelves are easily removable and adjustable in height, without the use of any tool, as they fit into a series of fixed height slots
- Shelf dimensions (W x D cm) : 65 x 50
 - Shelf loading capability (Kg) : 30 (with uniformly stored material)
- **Internal lighting** : Nr 1 neon tube, located in the ceiling of the storage chamber, with automatic activation through a special switch located on the control panel
- **Control panel** : located in the top part of the structure (above the door) is compounded by the main switch, lighting switch and digital electronic

thermostat with incorporated alarm

- Main switch : appliance's ON/OFF switch, adjustable in 2 positions, it became illuminated when on the position ON
- Lighting switch : to light the internal illumination of the cabinet, adjustable in 2 positions (ON/OFF), it became illuminated when on the position ON
- Digital electronic thermostat with incorporated alarm : microprocessor operating, with 4 switches, allowing the control of all the freezer functions (maintaining of the set temperature, defrostings, compressor and fans functioning). The internal temperature is displayed with a LED display, with red colour, bright indication and an accuracy of 0,1°C. Into its functions, the thermostat includes even an alarm, both acoustic (with a buzzer) and visual (with indication LED dots) for temperature deviations, both over or below than the programmed one, with limits that remains adjustable according to the user needs. The acoustic alarm can be even muted through a special switch
- **Cooling unit** : bottom mounted, with the condensing unit compounded by Nr 1 hermetic compressor and Nr 1 wire condenser, air cooled through a fan. Also, in the ceiling of the storage chamber, is mounted the finned evaporator with copper pipes, that is housed into a plastic cover that incorporate the fan. All the mounted components are industrial grade to grant the maximum reliability
- **Refrigerant** : R404a CFC-free
- **Refrigeration** : forced-air, through a fan, granting the maximum temperature uniformity and stability inside of the cabinet
- **Defrosting** : completely automatic, thermostat controlled. The condensate water is automatically channelled into an heated tray, located in the motor compartment, for the automatic evaporation of the condensate water
- **Temperature range** : infinitely adjustable between -5°C / -25°C
- **Voltage (V/ph/Hz)** : 220-230/1/50
- **Plug** : Schuko type
- **Breakers** : Nr 2 glass cartridge fuses with a rating of 10A, at protection of the appliance
- **Noise level (dB(A))** : ≤ 52
- **Gross capacity (litres)** : 670



BASIC LABORATORY FREEZER GLASS DOOR

BLFG 640

- **Net capacity (litres) :** 640
- **Dimensions (W x D x H cm) :** 78 x 73 x 187
- **Net weight (Kg) :** 110
- **Packed dimensions (W x D x H cm) :** 90 x 82 x 210 (1,55 m³)
- **Gross weight (Kg) :** 130



BASIC LABORATORY FREEZER GLASS DOOR

BLFG 640


ACCESSORIES AVAILABLE



Safety door lock with key



Temperature chart recorder



Wooden crate packing



Vers. July 13

* The declared performances are referred at +28°C ambient temperature, relative humidity of 70% and without any internal thermal mass (empty cabinet).

* Should it be necessary or useful without undermining any model essential features, technical and stylistic characteristics are subject to be changed without manufacturer's previous notice.